

TRANSPORTATION LIGHTING

For Models : All Commercial Vehicles




LED | LIGHTING CATALOG



ENGINEERED LIGHTING SOLUTIONS

Vision X lighting fixtures are not merely lighting systems, they are engineered lighting solutions. They provide increased efficiency, increased safety, decreased environmental impact, and decreased costs. Vision X LED lights offer a large increase in energy efficiency over older technologies while also increasing the safety and productivity of the working environment by outputting 80% more light than the fixtures used previously.




2D BLUEPRINT

Vision X Lighting begins each project with a customer provided list of vehicles to be retrofitted, then gathers the technical information for those vehicles.




3D MODEL

A 3D model is built to the customer's specifications, then carried over into the rendering.



SIMULATION RENDER

A simulation rendering ensures the final product will meet the customer's lighting requirements.



SOLUTION

Vision X Lighting creates a complete breakdown of the customer's specific needs to meet their lighting and safety requirements.



LONG HAUL TRUCK FITOUT GUIDE



DRIVING LIGHTING
SEALED BEAM WORK LIGHT
of Fixtures : **Vehicle Specific**
Location : **Front**
Finish : **Chrome, Black Chrome**
Part # : **XIL-46D**



MID-LONG RANGE LIGHTING
CANON GEN2 SERIES
of Fixtures : **Vehicle Specific**
Location : **Front**
Beam Pattern : **10°**
Part # : **CG2-CPM1810** (Mid-Range)
CGS-CPZ610 (Long-Range)



BACK-UP/ LOAD LIGHTING
VW-SERIES
of Fixtures : **Vehicle Specific**
Location : **Back**
Housing : **Oval, Round, Square**
Part # : **VW0050640** (Oval)
VWR040540 (Round)
VWS030440 (Square)



BACK-UP/ LOAD LIGHTING
DURA-SERIES
of Fixtures : **Vehicle Specific**
Location : **Back**
Beam Pattern : **10/ 40/ 60°**
Part # : **DURA-410** (Dura 4)
DURA-610 (Dura 6)



BACK-UP/ LOAD LIGHTING
UMX-SERIES
of Fixtures : **Vehicle Specific**
Location : **Back**
Beam Pattern : **10/ 40/ 60°**
Part # : **XIL-UMX4010** (Round)
XIL-UMX4410 (Square)



FORWARD LIGHTING

Product Information

Project Name:
Date:
Type:

Application

Not everyone gets the luxury of driving to work during the daytime. Upgrading your forward facing lights will allow you to get to your destination safely and help reduce eye-strain for those long hauls.

SPECIFICATIONS

Mechanical Information:

| | |
|------------------|-------------------|
| Fixture Weight: | 1.95 lbs (0.88kg) |
| Shipping Weight: | 2.9 lbs (1.34kg) |
| Mounting: | Fits OEM Brackets |

Electric Specifications:

| | |
|--------------------|---------------|
| Operating Voltage: | 9-32V DC |
| Wattage: | 42W |
| Operating Temp: | -40°C ~ 85°C |
| Vibration: | 60Grms |
| Connector: | 2 Pin Deutsch |

Construction:

| | |
|-------------------|----------------------|
| Housing: | Hybrid Housing |
| Reflector Finish: | Chrome, Black Chrome |
| Beam Modes: | Halo, Low, High |

LED

| | |
|-----------|------------|
| LED: | XP-L(CREE) |
| Amp Draw: | 3.5A @12V |
| Lifespan: | 50,000 hr |

RATINGS:

| | |
|---------------------|----------|
| DOT | Approved |
| Ingress Protection: | IP-68 |



4X6” LED HEADLIGHT

| PART #: | FINISH |
|-------------|--------------|
| 1 XIL-46D | Chrome |
| XIL-46DKIT | Chrome |
| XIL-46DB | Black Chrome |
| XIL-46DBKIT | Black Chrome |



7” LED HEADLIGHT

| PART #: | FINISH |
|-------------|--------------|
| XIL7RD | Chrome |
| XIL-7RDKIT | Chrome |
| XIL-7RDB | Black Chrome |
| XIL-7RDBKIT | Black Chrome |





FORWARD LIGHTING MID-RANGE

Product Information

Project Name:
Date:
Type:

Application

From 3.7” to 8.7” sizes, each is available in a Long Distance or Multi-LED Full Beam version to shine the light exactly where you need it. The Day-White lighting color allows you to comfortably see the terrain over the unmatched distances. The 25-Lights-In-One cover system allows you to change light pattern and color to fit your driving environments.

SPECIFICATIONS 6.7” MID RANGE DRIVING LIGHT

Mechanical Information:

| | |
|------------------|-------------------|
| Fixture Weight: | 7.05 lbs (3.19kg) |
| Shipping Weight: | 8.32 lbs (3.77kg) |
| Mounting: | Single Bolt |

Electric Specifications:

| | |
|--------------------|---------------|
| Operating Voltage: | 9-32V DC |
| Wattage: | 126W |
| Operating Temp: | -40°C ~ 85°C |
| Distance to 1 Lux: | 1,105 Ft. |
| Connector: | 2 Pin Deutsch |

Construction:

| | |
|----------|--------------------|
| Housing: | Hybrid Housing |
| Finish: | Gloss Black |
| Lens: | Polycarbonate Lens |

LED

| | |
|-----------|------------|
| LED: | XP-L(CREE) |
| Amp Draw: | 10.5A @12V |
| Lifespan: | 50,000 hr |


RATINGS:

| | |
|---------------------|----------|
| DOT | Approved |
| Ingress Protection: | IP-68 |



| PART #: | BEAM |
|----------------------|------|
| 2 CG2-CPM1810 (6.7) | 10° |
| CGS-CPM1810KIT (6.7) | 10° |
| CG2-CPM710 (4.5) | 10° |
| CG2-CPM710KIT(4.5) | 10° |

2D DRAWING:



FORWARD LIGHTING LONG-RANGE

Product Information

Project Name:
Date:
Type:

Application

From 3.7” to 8.7” sizes, each is available in a Long Distance or Multi-LED Full Beam version to shine the light exactly where you need it. The Day-White lighting color allows you to comfortably see the terrain over the unmatched distances. The 25-Lights-In-One cover system allows you to change light pattern and color to fit your driving environments.

SPECIFICATIONS 6.7” LONG RANGE DRIVING LIGHT

Mechanical Information:

| | |
|------------------|-------------------|
| Fixture Weight: | 5.73 lbs (2.59kg) |
| Shipping Weight: | 6.82 lbs (3.09kg) |
| Mounting: | Single Bolt |

Electric Specifications:

| | |
|--------------------|---------------|
| Operating Voltage: | 9-32V DC |
| Wattage: | 70W |
| Operating Temp: | -40°C ~ 85°C |
| Distance to 1 Lux: | 3,000 Ft. |
| Connector: | 2 Pin Deutsch |

Construction:

| | |
|----------|--------------------|
| Housing: | Hybrid Housing |
| Finish: | Gloss Black |
| Lens: | Polycarbonate Lens |

LED

| | |
|-----------|------------|
| LED: | XP-L(CREE) |
| Amp Draw: | 5.83A @12V |
| Lifespan: | 50,000 hr |


RATINGS:

| | |
|---------------------|----------|
| DOT | Approved |
| Ingress Protection: | IP-68 |



| PART #: | BEAM |
|---------------------|------|
| 2 CGS-CPZ610 (6.7) | 10° |
| CGS-CPZ610KIT (6.7) | 10° |
| CG2-CPZ110 (4.5) | 10° |
| CG2-CPZ110KIT (4.5) | 10° |

2D DRAWING:





REVERSE | LOAD LIGHTING

Product Information

Project Name:
Date:
Type:

Application

The Duralux Series gives more output than 100W Halogen lights while drawing much less power and reducing wear on associated components. Additionally, the Duralux was designed with fleet vehicles in mind, reducing cost, energy consumption, and boosting output at an attractive price.

SPECIFICATIONS DURALUX 4 LED

Mechanical Information:

| | |
|------------------|-------------------|
| Fixture Weight: | 1.50 lbs (0.68kg) |
| Shipping Weight: | 2.6 lbs (1.18kg) |
| Mounting | Single Bolt M6 |

Electric Specifications:

| | |
|--------------------|---------------|
| Operating Voltage: | 11 - 65VDC |
| Wattage: | 20W |
| Operating Temp: | -40°C - 80°C |
| Vibration: | 15.6Grms |
| Connector: | 2 Pin Deutsch |

Construction:

| | |
|----------|------------------------|
| Housing: | Die-Cast 6061 Aluminum |
| Finish: | Gloss Black |
| Lens: | Polycarbonate Lens |

LED

| | |
|-----------|-----------|
| LED: | LG |
| Amp Draw: | 1.6A @12V |
| Lifespan: | 50,000 hr |


RATINGS:

| | |
|---------------------|---|
| EMC Emission: | (CISPR 25) Edition 3.0 (2008-03) Class 3 |
| Ingress Protection: | IP-68, IP69k |



| ITEM #: | BEAM PATTERN |
|------------|--------------|
| 3 DURA-410 | Flood 10° |
| DURA-440 | Flood 40° |
| DURA-460 | Flood 60° |

2D DRAWING:



FLUSH MOUNT
AVAILABLE



REVERSE | LOAD LIGHTING

Product Information

Project Name:
Date:
Type:

Application

Available in three different housing sizes and three different beam patterns, the Duralux Series is one of the most adaptive fixtures made by Vision X. The Die-Cast Aluminum housing combines durability with affordability for a wide variety of applications.

SPECIFICATIONS DURALUX 6 LED

Mechanical Information:

| | |
|------------------|-------------------|
| Fixture Weight: | 2.63 lbs (1.19kg) |
| Shipping Weight: | 3.8 lbs (1.72kg) |
| Mounting | Single Bolt M6 |

Electric Specifications:

| | |
|--------------------|---------------|
| Operating Voltage: | 11 - 65VDC |
| Wattage: | 30W |
| Operating Temp: | -40°C - 80°C |
| Vibration: | 60 Grms |
| Connector: | 2 Pin Deutsch |

Construction:

| | |
|----------|------------------------|
| Housing: | Die-Cast 6061 Aluminum |
| Finish: | Gloss Black |
| Lens: | Polycarbonate Lens |

LED

| | |
|-----------|-----------|
| LED: | LG |
| Amp Draw: | 2.5A @12V |
| Lifespan: | 50,000 hr |


RATINGS:

| | |
|---------------------|---|
| EMC Emission: | (CISPR 25) Edition 3.0 (2008-03) Class 3 |
| Ingress Protection: | IP-68, IP69k |



| ITEM #: | BEAM PATTERN |
|------------|--------------|
| 3 DURA-610 | Flood 10° |
| DURA-640 | Flood 40° |
| DURA-660 | Flood 60° |

2D DRAWING:



FLUSH MOUNT
AVAILABLE





REVERSE | LOAD LIGHTING

Product Information

Project Name:
Date:
Type:

Application

The VW-Series LED Light Duty offers outstanding light output in a functional design which can be easily adjusted with the single bolt bracket. High quality construction and components enable VW-Series LED Light Duty to withstand vibration up to 15.6 Grms. Built-in reverse polarity protection helps prevent accidental damage caused by incorrect installation. VW-Series LED Light Duty work lighting is a high value, versatile range designed for many light duty commercial applications.

SPECIFICATIONS VW SERIES

Mechanical Information:

| | |
|------------------|-------------------|
| Fixture Weight: | 1.50 lbs (0.68kg) |
| Shipping Weight: | 2.6 lbs (1.18kg) |
| Mounting | Single Bolt M6 |

Electric Specifications:

| | |
|--------------------|---------------|
| Operating Voltage: | 11 - 65VDC |
| Wattage: | 20W |
| Operating Temp: | -40°C - 80°C |
| Vibration: | 15.6Grms |
| Connector: | 2 Pin Deutsch |

Construction:

| | |
|----------|------------------------|
| Housing: | Die-Cast 6061 Aluminum |
| Finish: | Gloss Black |
| Lens: | Polycarbonate Lens |

LED

| | |
|-----------|-----------|
| LED: | LG |
| Amp Draw: | 1.6A @12V |
| Lifespan: | 50,000 hr |

RATINGS:

| | |
|---------------------|---|
| EMC Emission: | (CISPR 25) Edition 3.0 (2008-03) Class 3 |
| Ingress Protection: | IP-68, IP69k |



OVAL



ROUND



SQUARE

| ITEM #: | BEAM | LEDs |
|--------------------|------|------|
| 3 VW0050640 (Oval) | 40° | 6 |
| VW0050840 (Oval) | 40° | 8 |
| VWR040540 (Round) | 40° | 5 |
| VWR050640 (Round) | 40° | 6 |
| VWR050940 (Round) | 40° | 9 |
| VWS030440 (Square) | 40° | 4 |
| VWS040540 (Square) | 40° | 5 |
| VWS050640 (Square) | 40° | 6 |
| VWS050940 (Square) | 40° | 9 |



REVERSE | LOAD LIGHTING

Product Information

Project Name:
Date:
Type:

Application

Simple quick connect wiring allows for one time wiring and no further electrical wiring to change the fixture. Industry leading LED light output, size, weight and reliability for reduced unscheduled maintenance.

SPECIFICATIONS UMX SERIES

Mechanical Information:

| | |
|------------------|-------------------|
| Fixture Weight: | 2.65 lbs (1.2kg) |
| Shipping Weight: | 3.56 lbs (1.61kg) |
| Mounting | Single Bolt M6 |

Electric Specifications:

| | |
|--------------------|---------------|
| Operating Voltage: | 11 - 65VDC |
| Wattage: | 35W |
| Operating Temp: | -40°C - 80°C |
| Vibration: | 15.6Grms |
| Connector: | 2 Pin Deutsch |

Construction:

| | |
|----------|------------------------|
| Housing: | Die-Cast 6061 Aluminum |
| Finish: | Gloss Black |
| Lens: | Polycarbonate Lens |

LED

| | |
|-----------|-----------|
| LED: | LG |
| Amp Draw: | 1.6A @12V |
| Lifespan: | 50,000 hr |

RATINGS:

| | |
|---------------------|---|
| EMC Emission: | (CISPR 25) Edition 3.0 (2008-03) Class 3 |
| Ingress Protection: | IP-68, IP69k |




XIL-UMX40xx

XIL-UMX44xx

| ITEM #: | BEAM PATTERN |
|-----------------------|--------------|
| 3 XIL-UMX4010 (Round) | 10° |
| XIL-UMX4040 (Round) | 40° |
| XIL-UMX4060 (Round) | 60° |
| XIL-UMX4410 (Square) | 10° |
| XIL-UMX4440 (Square) | 40° |
| XIL-UMX4460 (Square) | 60° |

2D DRAWING:





ACCESSORIES

Product Information

Project Name:
Date:
Type:

Video Extreme Light Kit:

- Kit Available with 7" Monitor
- Glare Blocking Shield
- Infrared Model Available

| | |
|---------------------|-----------------------|
| Fixture Dimensions: | 4.71" x 6.28" x 3.14" |
| Fixture Weight: | 2.43lbs (1.10kg) |
| Wattage: | 30W |
| Amp Draw: | 2.5A @12V |
| Vibration Rating: | 15.6 Grms |
| Application: | Video Back-Up System |
| Lifespan: | 50,000hr |
| Operating Temp: | -40°C - 80°C |

RATINGS:

| | |
|---------------------|---|
| EMC Emission: | (CISPR 25) Edition 3.0 (2008-03) Class 3 |
| Ingress Protection: | IP-68, IP69k |



| ITEM #: | LED |
|--------------------------|-------|
| VEL-4460CA72SS | White |
| VEL-CAMMON7KIT | White |
| VEL-4460CA72SS. IR850 | IR |
| VEL-M7 (7" Monitor) | -- |

4.3" Utility Flood Light:

- 120° of Light Output
- 32 Wide Angle LEDs
- Flood Light for Universal Applications with Ultra Lightweight, Bright Design

| | |
|---------------------|-----------------------|
| Fixture Dimensions: | 3.52" x 1.91" x 0.91" |
| Fixture Weight: | 0.41lbs (0.19kg) |
| Wattage: | 6W |
| Amp Draw: | 0.5A @12V |
| Vibration Rating: | 8.6 Grms |

RATINGS:

| | |
|---------------------|---|
| EMC Emission: | (CISPR 25) Edition 3.0 (2008-03) Class 3 |
| Ingress Protection: | IP-68, IP69k |



| ITEM #: | COLOR |
|-----------|--------|
| XIL-UF32 | White |
| XIL-UF32A | Amber |
| XIL-UF32B | Blue |
| XIL-UF32G | Green |
| XIL-UF32R | Red |
| XIL-UF32P | Purple |



ACCESSORIES

Product Information

Project Name:
Date:
Type:

Strip Lighting Soft Touch

Touch Activated Strip Light Available in 7.5" and 12"

| | |
|---------------------|---|
| Fixture Dimensions: | 7.44" x 0.92" x 0.59" 11.93" x 0.92" x 0.59" |
| Wattage: | 2W (7.5") 4.2W (12") |
| Amp Draw: | 0.16A @12V (7.5") 0.35A @12V (12") |
| Vibration Rating: | 15.6 Grms |

RATINGS:

| | |
|---------------------|-------|
| Ingress Protection: | IP-68 |
|---------------------|-------|




| ITEM #: | SIZE |
|-----------|------|
| XIL-SL7.5 | 7.5" |
| XIL-SL12 | 12" |
| XIL-ST7.5 | 7.5" |
| XIL-ST12 | 12" |

Security Bolts

Security hardware reduces theft by requiring a special tool to remove.

- Fits Virtually Any Bolt
- 304 Stainless Steel Construction
- Sold as 2 Bolts with 1 Tool



| ITEM #: | SIZE |
|------------|---------|
| XIL-SB0615 | M6 X 15 |
| XIL-SB0620 | M6 X 20 |
| XIL-SB0815 | M8 X 20 |
| XIL-SB0820 | M8 X 20 |
| XIL-SB0825 | M8 X 25 |

Security Nuts

Security hardware reduces theft by requiring a special tool to remove.

- Fits Virtually Any Bolt
- Plated Carbon Steel Construction
- Sold as 2 Bolts with 1 Tool



| ITEM #: | SIZE |
|----------|------|
| XIL-SN06 | M6 |
| XIL-SN08 | M8 |
| XIL-SN10 | M10 |
| XIL-SN12 | M12 |



VISION X USA
1601 Boundary Blvd
Auburn WA 98001
United States of America
P: 253-218-2900
www.vxindustrial.com



VISION X ASIA
23-7 Dongtansandan
9-gil Dongtan-myeon Hwaseong-si
Gyeonggi-do 18487, Korea
P: 82-32-515-4814
www.visionxlighting.com